

# VOYAGE DECKING



ENHANCED  
TRACTION

Deco**r**ators® Voyage™ provides 34% or greater surface traction than other leading brands of composite decking\*

#### GET THIS LOOK

Voyage Costa decking with SLX Cable rail and Deco**r**ators® by Hinkley Luna step lights



STRONG



LIGHTWEIGHT



STABLE



WATER &  
GROUND

Voyage offers enhanced traction and beautiful vertical grain variegation in strong, lightweight and stable decking. Like other members of the Deco**r**ators® Eovations™ decking family, Voyage delivers the industry's best strength-to-weight ratio, absorbs virtually no moisture, and allows virtually no thermal expansion or contraction.

Voyage comes in four beautiful colors that are the most popular in outdoor living spaces among homeowners: Sierra (dark gray), Tundra (gray), Costa (golden brown) and Mesa (red brown). It is backed by a 25-year structural, 25-year stain-and-fade and 25-year removal-and-replacement limited warranty that covers water and ground contact.

SIERRA

TUNDRA

COSTA

MESA

\* Capped composite decking boards tested by an independent third-party lab in wet conditions under the AS/NZS 4586-2013 standard; decking boards were tested on 9/24/18-9/25/18.



**25** YEAR  
STAIN & FADE

**25** YEAR  
STRUCTURAL

**25** YEAR  
REMOVAL & REPLACEMENT

**LIMITED**  
WARRANTY

**GET THIS LOOK**

Voyage Sierra and Tundra decking with black lattice panels

**EOVATIONS™ TECHNOLOGY**

Deckorators® Voyage™ features a substrate made with patented Eovations™ technology. To define Eovations, it's easier to start with what it's not: wood or wood filled, vinyl, fiber cement or plastic composite. It's unlike any other decking on the market today. The extruded oriented process creates a fully fibrous product providing a durable, stable and water-resistant deck board with a superior strength-to-weight ratio. It won't splinter, sag, chalk or crack.



**SEE HOW DECKORATORS® VOYAGE™ STACKS UP AGAINST THE LEADING PVC DECKING:**

PROPERTY	Dec <span style="color:red">✕</span> orators® VOYAGE DECKING	LEADING PVC DECKING
Weatherability	YES	YES
Scratch-resistant	YES	YES
Stain-resistant	YES	YES
All ingredients unaffected by moisture, sun or microbes	YES	NO
Best stiffness-to-weight ratio of any thermoplastic deck board in the industry	YES	NO
Strength:weight ratio (MOR at ambient temp with no environmental or safety factors applied)	2608.7 (4200 psi, 1.61 lbs/lf)	2292.99 (3600 psi, 1.57 lbs/lf)
Cannot be broken in flexural loading or impact	YES	NO
Maximum deflection at midspan (Uniform load – 100 /sq. ft. at 16" o.c.)	0.03323062 (.835" x 5.5")	0.04067322 (1"x 5.5")
Lowest thermal expansion/contraction of any thermoplastic deck board in the industry	YES	NO
Thermal movement (50°F temp swing on a 12 ft deck board)	0.06768	0.17112
25-year removal and replacement warranty, including water and ground contact	YES	NO
Enhanced traction	YES	NO